

technical specifications	DOM ELSmobile software V4.0
--------------------------	-----------------------------

required operating system:	<ul style="list-style-type: none"> Windows XP, Vista
required PC hardware:	<ul style="list-style-type: none"> PC minimum 100 MB free disk space CD-ROM drive (only for installation) 1 free COM-interface display with screen resolution of 800x600 pixels
supported user languages:	<ul style="list-style-type: none"> German, English, French, Dutch, Spanish, Italian
compatibility to ELS software	yes, requires ELS software 4.2r4 or higher
interfaces to ELS software	<ul style="list-style-type: none"> TCP/IP (recommended) via LAN/WLAN/Internet infrared (DOM infrared adaptor required) COM port
interface to ELS devices	<ul style="list-style-type: none"> infrared via DOM infrared adaptor
interface to transponders	<ul style="list-style-type: none"> via DOM desk reader
administrable devices	200
administrable transponders	3000
administrable holidays	32
administrable vacations	15
administrable time zones	32 (time zones 1 to 31 changeable, time zone 32 fixed)
multi-user administration	no
password protection for administration	yes (third person can be instructed to program devices without accessing data: "to-do list")
data backup facility	yes (built-in backup function)
supported ELS devices (infrared)	DOM ELS-P, DOM AccessManager, DOM Protector
supported DOM((o))butler	none
supported ELS devices (inductive)	none
supported transponders	Hitag 1, Hitag 2, Hitag S, EM 4100/4102, EM 4450/4550, DEISTER 1, DEISTER 2
scope of delivery:	CD with software, manual in PDF format

These data correspond to the actual development status and are subject to change at any time without notice.